



OFFICIAL LISTING

NSF International Certifies that the products appearing on this Listing conform to the requirements of NSF/ANSI Standard 40 - Residential Wastewater Treatment Systems

This is the Official Listing recorded on May 20, 2015.

Presby Environmental, Inc.
143 Airport Road
Whitefield, NH 03598
800-473-5298
603-837-3826



Facility: Whitefield, NH

**Rated
Capacity
Gallons/Day Classification**

Model Number

Advanced Enviro-Septic® Treatment System [1] [2] [3]

AES-CTD-450	450 Class I
AES-CTD-600	600 Class I
AES-CTD-750	750 Class I
AES-CTD-900	900 Class I
AES-CTD-1050	1050 Class I
AES-CTD-1200	1200 Class I
AES-CTD-1350	1350 Class I
AES-CTD-1500	1500 Class I
AES-SPD-450	450 Class I
AES-SPD-600	600 Class I
AES-SPD-750	750 Class I
AES-SPD-900	900 Class I
AES-SPD-1050	1050 Class I
AES-SPD-1200	1200 Class I
AES-SPD-1350	1350 Class I
AES-SPD-1500	1500 Class I

Simple Septic® Treatment System [1] [2] [3]

SS-SPD 450	450 Class I
SS-SPD 600	600 Class I
SS-SPD 750	750 Class I
SS-SPD 900	900 Class I
SS-SPD 1050	1050 Class I
SS-SPD 1200	1200 Class I
SS-SPD 1350	1350 Class I
SS-SPD 1500	1500 Class I
SS-CPD 450	450 Class I
SS-CPD 600	600 Class I
SS-CPD 750	750 Class I
SS-CPD 900	900 Class I
SS-CPD 1050	1050 Class I
SS-CPD 1200	1200 Class I
SS-CPD 1350	1350 Class I

Note: Additions shall not be made to this document without prior evaluation and acceptance by NSF International.



SS-CPD 1500	1500 Class I
Enviro-Septic® Treatment System [1] [2] [3]	
ES-CTD-450	450 Class I
ES-CTD-600	600 Class I
ES-CTD-750	750 Class I
ES-CTD-900	900 Class I
ES-CTD-1050	1050 Class I
ES-CTD-1200	1200 Class I
ES-CTD-1350	1350 Class I
ES-CTD-1500	1500 Class I
ES-STD-450	450 Class I
ES-STD-600	600 Class I
ES-STD-750	750 Class I
ES-STD-900	900 Class I
ES-STD-1050	1050 Class I
ES-STD-1200	1200 Class I
ES-STD-1350	1350 Class I
ES-STD-1500	1500 Class I

[1] Prefix CTD denotes combined or bottomless discharge. Prefix SPD denotes single point discharge. Prefix AES denotes Advanced Enviro-Septic®. Prefix SS denotes Simple Septic®. Prefix ES denotes Enviro-Septic®.

[2] **Table A, Minimum Sizing and Dimensions**
NSF 40 Class I Certified Advanced Enviro-Septic® Models, Simple Septic®, & Enviro-Septic® Models

Model Number Septic	Design Daily Flow	Minimum Total Pipe Length (ft.)	Minimum Tank Size (gal.)
XX-SPD 450 & XX-CTD 450	450	150	1000
XX-SPD 600 & XX-CTD 600	600	200	1200
XX-SPD 750 & XX-CTD 750	750	250	1500
XX-SPD 900 & XX-CTD 900	900	300	1800
XX-SPD 1050 & XX-CTD 1050	1050	350	2100
XX-SPD 1200 & XX-CTD 1200	1200	400	2400
XX-SPD 1350 & XX-CTD 1350	1350	450	2700
XX-SPD 1500 & XX-CTD 1500	1500	500	3000

Maximum loading of 3.0 gallons per linear foot of AES, SS or ES pipe.
 Minimum spacing of pipe rows - eighteen inches (18") on center (i.e. minimum one-half foot (6") of system sand between pipe rows).
 Note: All models include 6 in. of system sand below pipes for treatment.

[3] While the Presby treatment system includes design specifications similar to a dispersal field, the scope of the NSF/ANSI Standard 40 Class I Certification does NOT include management methods for the treated effluent discharged from the system.